

PolySwitch® PTC Devices

Overcurrent Protection Device

PRODUCT: miniSMDC160F

DOCUMENT: SCD24884

REV LETTER: I

REV DATE: JULY 26, 2016

PAGE NO.: 1 OF 2

Specification Status: Released

Maximum Electrical Rating


Voltage: 9V_{DC}

Short Circuit Current: 100A

Notes:

- 1. All terminations are tin plated
- 2. Drawing not to scale

Marking:






TABLE I. DIMENSIONS:

	Α		В		С		D		E
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN
mm:	4.37	4.73	0.28	0.48	3.07	3.41	0.25	0.95	0.20
in:	(0.172)	(0.186)	(0.011)	(0.019)	(0.121)	(0.134)	(0.010)	(0.040)	(0.008)

TABLE II. PERFORMANCE RATINGS:

	CUR	RENT F	RATING	GS **		TIME TO TRIP **	RESISTANCE VALUES		TRIPPED-STATE POWER DISSIPATION**	
AMPERES		AMPERES		AMPERES		SECONDS	OHMS		WATTS AT	
AT 0°C		AT 20°C		AT 60°C		AT 20°C, 8A	AT 20°C		20°C, 9V	
HOLD	TRIP	HOLD	TRIP	HOLD	TRIP	MAX	MIN	MAX*	MAX	
1.89	3.78	1.60	3.20	1.10	2.20	1.0	0.03	0.10	0.8	

^{*} Maximum resistance is measured 1 hour after reflow.

Agency Recognition: UL, CSA, TÜV Reference Documents: PS300

Precedence: This specification takes precedence over documents referenced herein.

Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

Materials Information

ROHS Compliant

Directive 2002/95/EC Compliant **ELV Compliant**

Directive 2000/53/EC Compliant (Pb)

Halogen Free*

^{**} Values Specified were determined using PCB's with 0.030"X1.5 ounce copper traces.

^{*} Halogen Free refers to: Br≤900ppm, Cl≤900ppm, Br+Cl≤1500ppm



PolySwitch® PTC Devices

Overcurrent Protection Device

PRODUCT: miniSMDC160F

DOCUMENT: SCD24884

REV LETTER: I

REV DATE: JULY 26, 2016

PAGE NO.: 2 OF 2

Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for own applications. Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, military, aerospace, medical, life life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product document Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse.	esaving, ation.