

MQ SERIES P22TG-XXXXE4:1M 1.5 KV ISOLATED 5 W REGULATED SINGLE OUTPUT DIP24

Available Inputs:

24 and 48 VDC Wide Input 4:1

Available Outputs:

3.3, 5, 12, 15 and 18 VDC

Other specifications please enquire.

Electrical Specifications

(Typical at + 25° C, nominal input voltage, rated output current unless otherwise specified)

Input Specifications

Voltage range 9 - 36 VDC (24 VDC), 18 - 72 VDC (48 VDC)

Filter Pi Network

Isolation Specifications

Rated voltage 1500 Vdc

Leakage current 1 mA

Resistance 10⁹ Ohm

Capacitance 80 pF typ.

Output Specifications

Voltage accuracy +/- 1 % typ. +/-2% max.

Ripple and noise (at 20 MHz BW) 60 mV p-p, max.

Short circuit protection Continuous , restart automatic

Line voltage regulation +/- 0,5 % max.

Load voltage regulation +/- 0,5 % max.

Temperature coefficient +/- 0,02 % / °C

General Specifications

Efficiency 70 % to 85 %

Switching frequency 250 KHz, typ.

Environmental Specifications

Operating temperature (ambient) -40°C to +85°C

Storage temperature - 55 °C to + 125 °C

Derating See graph

Humidity Up to 90 %, non condensing

Cooling Free air convection

Physical Characteristics

Dimensions 31,75 x 20,32 x 10,16 mm

1,25 x 0,80 x 0,40 inches


Weight 26,0 g

Case material Nickel Coated Copper


Examples of Partnumbers/Modelcode

| PART NO. | INPUT VOLTAGE (VDC) Nominal | INPUT CURRENT NO LOAD | INPUT CURRENT FULL LOAD | OUTPUT VOLTAGE (VDC) | OUTPUT CURRENT (max. mA) | EFFICIENCY FULL LOAD (% TYP.) |
|-----------------|-----------------------------|-----------------------|-------------------------|----------------------|--------------------------|-------------------------------|
| P22TG-2405E4:1M | 9-36 | 14.5 | 274 | 5 | 1000 | 76 |
| P22TG-2415E4:1M | 9-36 | 14.5 | 260 | 15 | 333 | 80 |
| P22TG-4805E4:1M | 18-72 | 15.8 | 139 | 5 | 1000 | 75 |
| P22TG-4812E4:1M | 18-72 | 15.8 | 132 | 12 | 417 | 79 |
| P22TG-4815E4:1M | 18-72 | 15.8 | 130 | 15 | 333 | 80 |

Dimensions



Derating Graph and Pinning



Specification can be changed without notice.

Copyright PEAK electronics GmbH